PAGE 1/6

	SWING PAINTS LIMITED	
	2100 ST PATRICK STREET	
	MONTREAL, QC H3K 1B2	
	(514) 932-2157	
PRODUCT: WOOD PRESER	VATIVE	CODE: 2305
	1. IDENTIFICATION	
PRODUCT IDENTIFIER	DEX END CUT WOOD PRESERVATIVE	
PRODUCT CODE	230501, 230504	
RECOMMENDED USE	WOOD PRESERVATIVE	
SUPPLIER	SWING PAINTS LIMITED 2100 ST PATRICK STREET MONTREAL, QC H3K 1B2 CANADA 514-932-2157	
EMERGENCY PHONE NO	514-932-2157 8:00 - 17:00 EST	

2. HAZARDOUS IDENTIFICATION

Hazardous Classification of the substance or mixture

Flammable liquids	Category 3
Carcinogenicity	Category 2
Specific target organ toxicity, single exposure	Category 3
Aspiration toxicity	Category 1

Hazard pictograms



Signal Word: Danger

Hazard statements

Flammable liquid and vapor May cause drowsiness or dizziness May be fatal if swallowed and enters airways Suspected of causing cancer

Precautionary Statements

Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapors/spray Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Response

IF exposed or concerned: Get medical advice/attention IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage Keep container tightly closed Store in a well-ventilated place.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Other Information

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS				
CHEMICAL NAME	CAS #	WT %		
Stoddard Solvent	8052-41-3	50-80		
Distillates (petroleum), Hydrotreated Light	64742-47-8	20-50		
Copper naphthenate	1338-02-9	12-16		

Notes:

The Stoddard Solvent contains 1,2,4- Trimethylbenzene, CAS # 95-63-6 (1-5%), Xylene, CAS # 1330-20-7 (0.1- 0.9%), Ethylbenzene, CAS # 100-41-4 (0.1-0.5%), Naphthalene, CAS # 91-20-3 (0.1-0.5%), Nonane, CAS # 111-84-2 (1.0-5.0%) as part of it's composition.

4. FIRST-AID MEASURES

Description of first aid measures

General advice

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

Inhalation

Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Ingestion

ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed:

Low toxicity. Slightly irritating, but will not injure eye tissue. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis). High vapor/aerosol concentrations (attainable at elevated temperatures well above ambient) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects. Skin contact may aggravate an existing dermatitis condition.

Indication of any immediate medical attention and special treatment needed:

Note to physicians

The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use DRY chemicals, CO2, alcohol foam or water spray.

Special hazards arising from the substance or mixture

Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode. Emits toxic fumes under fire conditions. Combustible. Avoid spraying water directly into storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors.

Hazardous combustion products

Carbon monoxide. Carbon dioxide. Smoke

Special protective equipment for firefighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Ensure adequate ventilation.

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up

Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Flammable. Keep the containers closed when not in use. Empty containers may contain hazardous product residues. Handle and open containers with care. Ensure proper electrical grounding procedures are in place. DO NOT handle or store near an open flame, heat, or other sources of ignition. Protect material from direct sunlight. Material will accumulate static charges which may cause an electrical spark (ignition source). DO NOT pressurize, cut, heat, or weld containers. DO NOT reuse empty containers with out commercial cleaning or reconditioning.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, away from heat and ignition sources.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

CHEMICAL NAME	EXPOSURE LIMIT ACGIH
Stoddard Solvent 8052-41-3	100 ppm TLV-TWA
Distillates (petroleum), Hydrotreated Light 64742-47-8	Not Available
Copper naphthenate 1338-02-9	200 ppm TLV-TWA

Consult local authorities for recommended exposure limits.

Appropriate engineering controls

Engineering controls

Local exhaust ventilation as necessary to maintain exposures to within applicable limits. In the laboratory environment, this product should be handled in a hood. Provide mechanical ventilation in confined spaces.

Individual protection measures

Eye/face protection

Safety glasses with side shields.

Hand protection

Impervious gloves.

Skin and body protection

The selection of personal protective equipment varies depending upon conditions of use.

Respiratory protection

If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical pr	operties
Appearance	I familia
Physical state	Liquid
Colour	Green
Odour	No data available
Odour threshold	No data available
рН	No data available
Melting point / freezing point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Flammability Limit in Air	
Upper flammability limit	No data available
Lower flammability limit	No data available
Vapor pressure	No data available
Relative vapor density	No data available
Specific gravity	0.8
Water solubility	No data available
Solubility in other solvents	No data available
Partition coefficient	No data available
Autoignition temperature	No data available
Decomposition temperature	No data available
Explosive properties	No data available
Oxidizing properties	No data available

10. STABILITY AND REACTIVITY

Reactivity/Chemical Stability Stable.

Possibility of hazardous reactions No additional remark.

Hazardous polymerization Will not occur.

Conditions to avoid

Avoid excessive heat, open flames and all ignition sources.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide. Toxic fumes. Smoke.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation

High vapor/aerosol concentrations (attainable at elevated temperatures well above ambient) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects.

Eye contact

Slightly irritating, but will not injure eye tissue.

Skin contact

Low toxicity. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Skin contact may aggravate an existing dermatitis condition.

Ingestion

Low toxicity. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death.

Information on toxicological effects

Symptoms

Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Numerical measures of toxicity

CHEMICAL NAME	ORAL LD50	DERMAL LD50	INHALATION LC50
Stoddard Solvent 8052-41-3	Not available	Not available	Not available
Distillates (petroleum), Hydrotreated Light 64742-47-8	>5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>5.2 mg/L (Rat) 4 h
Copper naphthenate 1338-02-9	2000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	Not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Low toxicity. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Skin contact may aggravate an existing dermatitis condition.

Serious eye damage/eye irritation

Slightly irritating, but will not injure eye tissue.

Respiratory or skin sensitization

No information available.

Germ cell mutagenicity

Classification based on data available for ingredients. Contains a known or suspected mutagen.

Carcinogenicity

This product contains ethylbenzene. The International Agency for Research on Cancer has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans.

INGREDIENTS	ACGIH	IARC	NTP	OSHA
Stoddard Solvent 8052-41-3	Not available	Not available	Not available	Not available
Distillates (petroleum), Hydrotreated Light 64742-47-8	Not available	Not available	Not available	Not available
Copper naphthenate 1338-02-9	Not available	Not available	Not available	Not available

Reproductive Toxicity

No information available.

Specific target organ systemic toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ systemic toxicity - repeated exposure No information available.

Aspiration hazard

May be fatal if swallowed and enters airways.

12. ECOLOGICAL INFORMATION

Ecotoxicity

CHEMICAL NAME	Ecotoxicity – Freshwater Algae (EC50)	Ecotoxicity - Fish Species (LC50)	Toxicity - Microorganisms	Ecotoxicity - Crustacea (EC50)
Stoddard Solvent 8052-41-3	Not available	Not available	Not available	Not available
Distillates (petroleum) Hydrotreated Light 64742-47-8	Not available	2.2 mg/L, 96h static (Lepomis macrochirus) 2.4 mg/L, 96h static (Oncorhynchus mykiss) 45 mg/L, 96h flow (Pimephales promelas)	Not available	Not available
Copper naphthenate 1338-02-9	Not available	Not available	Not available	Not available

Persistence and degradability

No information available.

Biodegradability

No information available.

Other adverse effects:

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation. Do not reuse empty containers.

14. TRANSPORT INFORMATION

TDG (Canada):UN NumberUN 1306Shipping nameWOOD PRESERVATIVE, LIQUIDClass3Packing GroupIIIMarine pollutantNo

DOT (U.S.)	
UN Number	UN 1306
Shipping name	WOOD PRESERVATIVE, LIQUID
Class	3
Packing Group	111
Marine pollutant	No

15. REGULATORY INFORMATION

Canadian Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. OTHER INFORMATION

PREPARED BY	Regulatory Affairs
PREPARATION DATE	June 1, 2018

Swing Paints expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

Do not use ingredient information and/or ingredient percentages in this SDS as a product specification. For product specification information refer to a Product Specification Sheet and/or a Certificate of Analysis.

All information appearing herein is based upon data obtained from the manufacturer and/or recognized technical sources. While the information is believed to be accurate, Swing Paints makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Swing Paints' control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

©2018 Swing Paints Ltd. All rights reserved.

End of Safety Data Sheet